



KAHLES

# K18i-2 SPLIT-SECOND PRECISION.



1-8x24i

The K18i-2 takes the class-leading field of view of the predecessor and expands it even further, giving shooters unmatched awareness in dynamic, short-range scenarios. Designed for speed and clarity, it provides competitive shooters and tactical professionals with split-second precision and maximum responsiveness.

## PRODUCT HIGHLIGHTS

- ◆ Ergonomics specifically designed for IPSC and 3-gun.
- ◆ True 8x zoom with real 1x magnification.
- ◆ VISIONFLEX – Revolutionary optical design with an **18%** wider field of view\* and a remarkably generous eyepiece.
- ◆ Illuminated reticle in second focal plane with MAXLIGHT function for extreme backlight situations.

## FEATURES



Second focal plane



MAXLIGHT



Main tube diameter 34 mm



MIL



Adjustment direction CW



Windage right



Interchangeable Throw Lever



VISIONFLEX




\* Based on the comparison to K18i at 1x.

## OPTIONAL



BALLISTIC TURRET

## RETICLES



3GR

SCAN TO EXPLORE  
OUR PORTFOLIO.





K A H L E S

## K18i-2

### TECHNICAL DATA

Focal plane	SFP
Magnification	1-8
Objective lens diameter (mm)	24
Field of view (m/100 m)	50,0-6,2
Exit pupil diameter (mm)	8,1-3,0
Eye relief (mm)	95
Diopter compensation (dpt)	+2/-3
Twilight factor (DIN 58388)	4,9-13,9
Parallax adjustment (m)	100
Impact correction / Click E/W	.1 MRAD
Clicks / Revolution E/W	60/60
Adjustment range E/W (m/100 m)	2,4/2,4
Adjustment direction	CW
Windage	right
Maintube diameter (mm)	34
Length (mm)	300
Weight (g)	640
Battery type	CR2032
Objective filter thread	M30 x 0,75
Reticles	3GR
Illumination	✓
VISIONFLEX	✓
MAXLIGHT	✓
Ballistic Turret (optional)	✓
Waterproof (ISO9022-8)	✓
Accessories (optional)	Flip-Up Cover Objective 24 mm / Ocular 52 mm, Bubble Level 34 mm, Ballistic Turret BT K-1

SCAN FOR PRICES,  
USER MANUAL &  
SERVICE SECTION.

